

DEWATERING COMPOUND

Combined dewatering compound and rust preventative.

PRODUCT SPECIFICATION

Appearance	:	Red – brown liquid
Odour	:	Slightly hydrocarbon
Density	:	0.88
Flash Point	:	33°C (closed up)
Boiling Point	:	150 - 190°C

FEATURES AND BENEFITS

- ◆ Very effective rust preventative which provides corrosion protection for goods stored internally for periods of up to 90 days.
- ◆ Multiple product – dries and protects in one operation. As the product contains a water displacement product, it is possible to treat parts without previous drying.
- ◆ Quick – drying.
- ◆ The film left on metal surfaces is almost imperceptible and will not normal affect further operations. If required, the film may be removed with an appropriate Chemical Formulators solvent cleaner.

USE DIRECTIONS

Parts from alkaline cleaning, degreasing and machining are sprayed, dipped or swabbed with undiluted Dewatering Compound. This provides up to 90 days corrosion-free internal storage.

Operational Hints

- Where work is of irregular shape or has internal cavities, it is recommended that the product be applied by immersion techniques.
- Never immerse hot articles in the product.
- Where immersion baths are used, an outlet at the bottom of the tank should be provided for the removal of water.

Packages

25 litre drums

03/06PI